

4000 Series

Model	Height Inches	Width Inches	Depth Inches	Door Type	Compressor HP.	Amps	Temperature Range (°F)	Refrigerant Gas	Units per 45' container
4304-SC	54 1/4	46	33 1/4	Sliding	1/4	7.0	35	R-134a	20
4306-SC	54 1/4	70	33 1/4	Sliding	1/3	10.0	35	R-134a	14
4308-SC	54 1/2	94	33 1/4	Sliding	1/2	10.5	35	R-134a	10
4310-SC	54 1/2	118	33 1/4	Sliding	1/2	12.0	35	R-134a	8

5000 Series

Model	Height Inches	Width Inches	Depth Inches	Number and type of doors	Compressor HP.	Amps	Temperature Range (°F)	Refrigerant Gas	Units per 45' container
5004-SC	52	46	33 1/2	2 Sliding - 1 Swing	1/4	8.0	32 / 39	R-134a	20
5006-SC	52	70	33 1/2	2 Sliding - 2 Swing	1/3	9.0	32 / 39	R-134a	14
5008-SC	52	94	33 1/2	2 Sliding - 2 Swing	1/2	12.0	32 / 39	R-134a	10
5010-SC	52	118	33 1/2	4 Sliding - 3 Swing	3/4	12.0	32 / 39	R-134a	8

ZEPHYR Series

Model	Height Inches	Width Inches	Depth Inches	Number and type of doors	Compressor HP.	Amps	Temperature Range (°F)	Refrigerant Gas	Units per 45' container
4-Z-SC	42 1/4	46	33 1/4	2 Sliding - 1 Swing	1/4	8.0	32 / 39	R-134a	40
6-Z-SC	42 1/4	70	33 1/4	2 Sliding - 2 Swing	1/3	10.0	32 / 39	R-134a	28
8-Z-SC	42 1/4	94	33 1/4	2 Sliding - 2 Swing	1/2	12.0	32 / 39	R-134a	20
10-Z-SC	42 1/4	118	33 1/4	4 Sliding - 3 Swing	1/2	12.0	32 / 39	R-134a	16



Display Cases



Features

- Available in 6', 8' and 10' length.
- Extra large 22" high triple pane hermetically sealed glass display front.
- Adjustable 10"-wide gleaming stainless steel mezzanine shelf.
- Service side-large multi pane easy glide sliding glass door upper section and solid insulated doors in lower section.
- Standard electric 115/1/60 easy plug in operation and (3) wire power cord.
- Non-corrosive stainless steel interior floor.
- Foamed-in-place polyurethane insulation.

